

Model 8200WC barrier-free combination shower and eye/face wash features a 10-5/8" ABS plastic showerhead and an ABS plastic Omni-Flo wrap around eye/face wash. A pull rod activates shower. Push flag activates eyewash. Pipe and fitting: 1-1/4" Schedule 40 hot-dipped galvanized steel. Supply and Waste: 1-1/4" IPS.

Model 8200WC is certified by CSA to meet the ANSI Z358.1 Standard for Emergency Eyewash and Shower Equipment.

Components:

Shower Head: Model 8129FC green ABS plastic 10-5/8" showerhead with integral 20 gpm flow control.

Shower Valve: Part number 0006575890 is a chrome-plated brass stay-open ball valve, equipped with a stainless steel ball and stem. Full flow occurs with pull on lever. 1"IPS.

Pull Rod: Model SP202 44" long stainless steel pull rod with triangular handle.

Eye/Face Wash Head Assembly: Model SP70 ABS plastic Omni-Flo wrap-around eye/face wash assembly. Spray head provides superior spray pattern that gently covers entire facial area.

Eyewash Flow Control: Model SP42 6.25 gpm flow control assembly. Controls water flow rate when flowing pressure is between 30 and 90 psi.

Dust Cover: Model 9090 yellow plastic dust cover that fully covers Omni-Flow face spray.

Receptor: Part Number 0001005231 green molded ABS plastic oval receptor resistant to damage from alkalis, salt solution, oils, most acids, sun exposure, and color change.

Eyewash Valve: Model SP225 chrome-plated brass stay-open ball valve, equipped with a stainless steel ball and stem. Full flow occurs with push on stainless steel flag. 1/2" IPS inlet x 1/4" IPS outlet.

In-Line Strainer: Model SP507 chrome-plated brass in-line 50 x 50 mesh water strainer that prevents debris from reaching the eye/face wash. Easily serviceable. 1/4" IPS inlet x 1/4" IPS outlet.

Mounting: Model SP75 gray powder-coated cast-iron 9" diameter floor flange with 1-1/4" IPS hot-dipped galvanized tee.

Universal Sign: Model SP178 vertical universal combination emergency shower and eyewash sign. Size: 8" x 10-3/4".

High-Visibility Stripe: Model SP185 self-adhesive high visibility 21" long stripe in Safety Green and bright yellow.

Test This Week Tag: SP170 is a green waterproof test card with space for date and initials of inspector. Used to record weekly testing of emergency equipment.

8200WC



Options/Accessories: (Additional costs may apply)

Combination Unit: Model 8200 combination shower and hand-or-foot activated Omni-Flow eye/face wash.

Hose & Spray Unit: Model 8901RFK body spray with 8-foot pressure rated hose. Includes retrofit kit to accommodate installation on many combination showers and eyewash units.

Tempered Water Blending Systems: Model TWBS.SH has fail-safe features, prepackaged, fully engineered and tested system for mixing large volumes of hot and cold water.

Tempered Water Blending Valves: Model 9202 thermostatic mixing valve that mixes hot and cold water for the tempering of water for eyewash and showers. Maximum flow rate is 40 gpm.

Shower Head: Model 8127FC corrosion-resistant 10-1/2" stainless steel showerhead with integral 20 gpm flow control.

Alarm: Model 9001 120 VAC emergency alarm and light system. Buzzer and flashing light are activated by flow switch when emergency shower or eyewash is in use.

Privacy Curtain: Model 9037 privacy curtain designed to be used on horizontal emergency drench shower or combination emergency drench shower and eyewash units.

CRP Protective Coating: CRP special green powder-coating provides extra protection against corrosive environments.

Universal Sign: Model 9020 green and yellow ABS plastic 3-sided sign for use with combination shower and eyewashes.

DISCLAIMER: Continued product improvements make specifications subject to change without notice. Check www.hawsco.com for the latest product information and updates.